


ELEVATION

NOTES (CONTINUED)

5. STRANDS OF BARBED TO BS EN 10223-1 FIXED TO STRAINING POSTS WITH 250x10 GALVANISED EYE BOLTS AND INTERMEDIATE POSTS WITH 38 x 4 GALVANISED STAPLES.
6. NO. OF STRANDS OF BARBED WIRE TO BE AGREED WITH THE FARMER.
7. FENCE SHALL BE ERECTED IN ACCORDANCE WITH BS 1722 PART 2.
8. SOFTWOOD POSTS AND RAILS SHALL BE TREATED WITH PRESERVATIVE IN ACCORDANCE WITH BS 8417. ALTERNATIVE POST TYPE: CONCRETE.
9. WHERE BARBED WIRE IS USED, A SITE SPECIFIC RISK ASSESSMENT SHALL BE CARRIED OUT TO IDENTIFY IF HAZARD WARNING SIGNAGE IS REQUIRED.



NOTES

1. THIS DRAWING TO BE READ IN CONJUNCTION WITH CS501 (CESWI 7th EDITION), CS501A (DCWW CIVIL SPECIFICATION) AND CS506 (DCWW SPECIFICATION FOR FENCING, GATES & BARRIERS).
2. 1950mm x 150mmØ STRAINING POST PLACED AT EACH CHANGE OF DIRECTION AND ACUTE VARIATION IN LEVEL, AND ON STRAIGHTS AT INTERVALS OF NO MORE THAN 150m. POST SHALL BE SET IN HOLE FILLED NOT LESS THAN 1/2 DEPTH WITH GEN 3 CONCRETE. FOR TEMPORARY FENCING, POST DRIVEN INTO GROUND MIN. 600mm - NO CONCRETE REQUIRED.
3. 1800mm x 100mmØ STRUT FITTED TO EACH STRAINING POST. POST SHALL BE SET IN HOLE FILLED NOT LESS THAN 1/2 DEPTH WITH GEN 3 CONCRETE. FOR TEMPORARY FENCING, POST DRIVEN INTO GROUND MIN. 600mm - NO CONCRETE REQUIRED.
4. 1800mm x 100mmØ INTERMEDIATE POSTS DRIVEN INTO GROUND MIN. 600mm.

I02	SECOND ISSUE	MC	SQ	GH	JAN. 2023
I01	FIRST ISSUE	TD	DW	RD	NOV. 2012
REV	REVISION	DRN	CHK	REVD	DATE



DCWW STANDARD DRAWING

GROUP:SDC2010

FENCES, HEDGES & BARRIERS

TITLE:

TIMBER POST STOCK PROOF FENCING

	INITIALS	DATE	SCALES
DRAWN BY:	MC	JAN. 2023	1:25
CHECKED BY:	SQ	JAN. 2023	
REVIEWED BY:	GH	JAN. 2023	

DIMENSIONS IN MILLIMETRES

A3

CLIENT DRAWING NO.

SDC2010/004

REV.

I02